

Project:
Type:
Catalog #:
By/Date:

Series 2002-K18000
Door Kickplate

Photoluminescent Exit Sign
Low Level • UL924 Listed • LEED Credit Compliant

Active Safety's Series 2002 K18000 is a unique door "kick-plate" with an integrated full size photoluminescent exit sign. A super durable and attractive 'die-cast' metal faceplate backed by a tough plastic liner make the 2002 K18000 an excellent option for a low level door mount exit sign in hotels, condos, schools, amusement parks, hospitals, US military facilities and other locations conforming to the IBC, NFPA and UFC codes.

Non-electrical, non-radioactive with a high content of recycled material, Active Safety Series 2002 K18000 photoluminescent exit signs will benefit LEED and other environmentally focused projects.

Photoluminescent operation means there are no electrical connections to engineer, procure and install. Located adjacent to fluorescent lighting, Series 2002 K18000 signs will operate for 25+ years with only minimal maintenance - no lamps, batteries or radioactive tubes to ever replace or dispose of.

Specification Features

Viewing Distance:	75 feet
Operating Life:	25+ years
Activation:	5 foot-candles of fluorescent lighting
Facing:	Heavy duty aluminum or stainless steel stenciled face
Facing Colors:	Black anodized, brushed aluminum, stainless steel or custom colors.
Letter Color:	Green Illuminating
Attachments:	Supplied by customer
Dimensions:	Height: 10" Width: 34", 40" or 46". Custom sizes available
Features:	Non-electrical, non-radioactive, low profile, explosion proof, low maintenance.
Warranty:	Limited lifetime warranty.
Listings & Codes:	Listed to UL924. Approved by California State Fire Marshal. Compliant to IBC, NFPA, IFC & UFC codes.
Green Attributes:	No hazardous materials, no radioactivity, activated by nearby light, high percentage of recycled material. Minimal maintenance. Long life.

Ordering Format (example: 2002 - K1800 - 36 - W - A)

SERIES	STYLE	SIZE	MOUNT LOCATION	COLOR
<u>2002</u>	<u>K18000</u>	<u>36</u> - 36" <u>40</u> - 40" <u>C</u> - custom	<u>W</u> - wood <u>G</u> - glass <u>M</u> - metal	<u>A</u> - Brushed Aluminum <u>S</u> - Stainless Steel <u>B</u> - Black Anodized Aluminum

Specification Description

High [or Low Level] Exit Sign. UL 924 listed. Photoluminescent, non-electrical, non-radioactive, 75 foot visibility rating, 25+ year life. Recycled aluminum or stainless steel construction. Die-cut, stenciled faceplate with green symbols. Single Face configuration for low level door mount application. **Active Safety Series 2002-K 18.000.**

