

**NON-ELECTRICAL
NON-RADIOACTIVE**

ACTIVE SAFETY™



USA 800.657.6324 fax: 801.265.9943
California 888.375.9684 fax: 831.625.8650
www.activesafety.com

Series 2002—BE16.000

Low Level Marker — Exit Sign

Stenciled Face with Polycarbonate Shield

Meets Los Angeles Unified School District Specifications

Features and Specifications

Features: Stenciled aluminum faceplate, photoluminescent non-radioactive panel, polycarbonate vandal resistant shield. Non-electrical, explosion proof, low maintenance. Easy/inexpensive installation.

Viewing Distance: 75 feet

Operating Expectancy: Twenty-five years+

Activation: 5 foot candles of fluorescent lighting

Facing: Heavy duty aluminum stenciled face with 1/16" polycarbonate shield

Facing Colors: Black, brushed aluminum, white or custom colors

Letter Size: 7/8" stroke with 7" height

Letter Color: Green Illuminating

Directional: Pop out chevron arrows

Mounting: Wall

Attachments: Tamper-proof metal screws

Dimensions: 8" high x 15" wide
Depth: 3/8"

Listing Reports: UL 924 (SA12885)
ICC - ESR1409
Intertek Testing Service (ETL) J99026743-001A
State of California Fire Marshal - 6200-1632:100
LA Research Report - RR25083

MODEL NUMBER

Wall Mount - single face

| | |
|------------------|--------------------|
| Brushed aluminum | 2002—BE16.000 SWMA |
| Black | 2002—BE16.000 SWMB |
| White | 2002—BE16.000 SWMW |

Please specify arrow direction for each sign.
[i.e. right arrow, left arrow, no arrow]



LISTED IN ACCORDANCE WITH UL924 STANDARD.