

**NON-ELECTRICAL  
NON-RADIOACTIVE**

ACTIVE



SAFETY™

USA 800.657.6324 fax: 801.265.9943  
California 888.375.9684 fax: 831.625.8650  
www.activesafety.com

## Series 2001

### High and Low Level Exit Sign Features and Specifications

- Features:** Attractive traditional design. Low Profile. Value priced. Non-radioactive. Heavy duty construction. Non-electrical. Explosion proof. Low maintenance. Easy, inexpensive installation.
- Viewing Distance:** 50 feet
- Operating Expectancy:** Twenty-five years+
- Activation:** 5 foot candles of fluorescent lighting
- Facing:** Green illuminating heavy duty PVC
- Frame:** Black anodized aluminum
- Letter Colors:** Red or Green
- Directional:** Field applied arrows (optional)
- Mounting:** Wall, flag or ceiling
- Attachments:** Tamper-proof metal screws
- Dimensions:** 8" high x 15" wide  
Depth: 1/8" - 3/8"
- Letter Size:** 7/8" stroke with 7" height
- Listing Reports:** UL 924 (SA12885)  
ICC - ESR1409  
Intertek Testing Service (ETL) J99026743-001A  
State of California Fire Marshal - 6200-1632-100  
LA Research Report - RR25083

### MODEL

#### Wall Mount - single face unframed

Green Letters 2001 USWMG  
Red letters 2001 USWMR

#### Wall Mount - single face framed

Green Letters 2001 SWMG  
Red letters 2001 SWMR

#### Ceiling/flag mount - single face

Green Letters 2001 SCMG  
Red letters 2001 SCMR

#### Ceiling/flag mount -double face

Green Letters 2001 DCMG  
Red letters 2001 DCMR



LISTED IN ACCORDANCE WITH UL924 STANDARD.

