

**NON-ELECTRICAL  
NON-RADIOACTIVE**

*ACTIVE*



*SAFETY™*

Utah 800.657.6324 fax: 801.265.9943  
California 888.375.9684 fax: 831.625.8650  
www.activesafety.com

## **Series 2002-K**

### Low Level Exit Sign KICK PLATE

#### **Features and Specifications**

- Features:** Heavy duty low profile design for high traffic areas.  
Non-electrical. Non-radioactive. Explosion proof.  
Low maintenance. Easy, inexpensive installation.
- Viewing Distance:** 75 feet
- Operating Expectancy:** Twenty-five years+
- Activation:** 5 foot candles of fluorescent lighting
- Facing:** Heavy duty aluminum or stainless steel stenciled face
- Facing Colors:** Black, brushed aluminum, stainless steel or custom colors
- Dimensions:** Height: 10"  
Width: 34", 40" or 46"  
Custom sizes available
- Letter Size:** 7/8" stroke with 7" height
- Letter Color:** Green Illuminating
- Attachment:** Specify type of door for attachment- wood, glass or aluminum
- Listing Reports:** UL 924 (SA12885)  
ICC - ESR1409  
Intertek Testing Service (ETL) J99026743-001A  
State of California Fire Marshal - 6200-1632:100  
LA Research Report - RR25083
- Model:** Kickplate  
Brushed aluminum 2002-18 KPMA  
Stainless steel 2002-18 KPMS  
Black 2002-18 KPMB



LISTED IN ACCORDANCE WITH UL924 STANDARD.  
STANDARD FOR EMERGENCY LIGHTING &  
POWER EQUIPMENT. ©2005

©2006

**USE ACTIVE SAFETY'S EXIT  
MODELS 2001 AND 2002  
FOR HIGH LEVEL APPLICATIONS**