

**NON-ELECTRICAL
NON-RADIOACTIVE**

ACTIVE



SAFETY™

Utah 800.657.6324

California 888.3759684 fax: 831.625.8650

www.activesafety.com

Series 39.5

Floor Level Pathway Striping

Features & Specifications

- Size:** 1" & 2" width
39.5" length
.030 depth
- Color:** Standard- Green Illuminating
- Activation:** 3-5 foot-candles ambient lighting
- Directional:** Optional arrows for one way exiting
- Life Expectancy:** Twenty-five years+
- Construction:** Aluminum backing with photoluminescent coating. Hi tack adhesive backing
- Attributes:** Non-electrical, non-radioactive, explosion proof, low maintenance
ASTM E 162 flame index: 22.88
- Listing Reports:** UL 1994 Classified
ICC - ESR1409
Los Angeles Research Report #RR-25083-T
US Test Report #182556-1
- Model:** Series 39.5-1", 39.5-2", 39.5-2"A



Series 11.000 PSL & LA

Floor Level Pathway Striping

Features & Specifications

- Marker Size:** 1.75" width, 52" length, 1/8" depth
- Color:** Standard- Green Illuminating
- Attachment:** Aluminum J-mold track
- Activation:** 3-5 foot-candles ambient lighting
- Directional:** Optional arrows for one way exiting only
- Life Expectancy:** Twenty-five years+
- Construction:** 11.000 PSL: PL Polystyrene laminate
11.000 LA: Self-illuminating coating on aluminum panel, Aluminum J-mold
- Attributes:** Non-electrical, non-radioactive, explosion proof, low maintenance
11.000 LA ASTM E 162 flame index: 22.88
- Listing Reports:** UL 1994 Classified
ICC - ESR1409
Los Angeles Research Report #RR-25083-T
US Test Report #182556-1
- Model:** Polystyrene 1.75 inch 11.000 PSL
Aluminum 1.75 inch 11.000 LA

