



ACTIVE SAFETY

SAFER • LESS EXPENSIVE • SUSTAINABLE

USA 800.657.6324

www.activesafety.com

Project:

Contact:

Catalog #:

Date:

Series 200 Photoluminescent Stair Tread Marker

Features

<p>Viewing Distance: 25 feet</p> <p>Operating Life: 25+ years</p> <p>Activation: 1 footcandle of artificial lighting including LED and Fluorescent.</p> <p>Marker Composition: Durable aluminum extrusion with photoluminescent stripe. Non slip metal seration or optional non-slip stripe and bullnose.</p> <p>Marker Color: Yellow-green illuminating</p> <p>Mounting: Client field applied construction adhesive and screws.</p> <p>Dimensions: Photoluminescent stripe width: 1/2", 1" or 2". Length: 36", 48" or custom. Overall profile width varies from 2.35 - 3" with bull-nosing</p> <p>Warranty: 5 years on materials, 25 years on glowing.</p> <p>Green Attributes: Non-electric. Non-radioactive. No hazardous materials. Long life. Near-zero maintenance.</p> <p>Listings and Codes: UL 1994 listed</p>	<p>Active Safety's Series 200 Stair Tread Marker is a durable "flat orbullnose" shaped extrusion that installs directly onto the leading edge of new and existing stairs in building exit path stairwells. Several model variations provide for a high quality installation consistent with building architecture and occupant traffic patterns. Automatic operation requires only 1 footcandle of charging illumination under normal conditions. Long life and near zero maintenance ensure the system will always be available to support tenant safety during normal operations and emergencies.</p>
-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Ordering Format (example: 200 – A L – B – 1 – 48)

SERIES	CONSTRUCTION	PROFILE	PHOTOLUMINESCENT STRIPE WIDTH	LENGTH
200 - Stair Tread Marker	<u>AL</u> - Aluminum <u>ALS</u> - Aluminum w/ non-skid stripe	<u>B</u> - Bullnose <u>E</u> - Flat	<u>1/2</u> - 1/2" <u>1</u> - 1"	<u>48</u> - 48" <u>C</u> - Custom

Specification Description

Photoluminescent Bullnose Stair Tread Marker. UL 1994 Listed. Compliant to IBC, NFPA & IFC Codes. Non-electrical, non-radioactive photoluminescent operation. Durable bullnose satin anodized aluminum extrusion is [36" or 48" or custom] long and comes [with/without a non-skid stripe]. Photoluminescent stripe is [1/2", 1" or 2"] wide. 25 foot visibility with 1 footcandle of charging illumination.

Active Safety Series 200. [Brackets denotes options]

