PHOTOLUMINESCENT • SERIES 210 • SUSTAINABLE • SAFER • LESS EXPENSIVE

ACTIVE SAFETY

SAFER•LESS EXPENSIVE•SUSTAINABLE

USA 800.657.6324

www.activesafety.com

Project:
Contact:
Catalog #:
Date:

Series 210 BA

Photoluminescent Stair Strip - Flat Profile

Features

Viewing Distance:	25 feet
Operating Life	25+ years
Activation:	1 foot-candle of artificial lighting.
Marker Composition:	Thin profile aluminum strip with photoluminescent coating.
Mounting:	Adhesive backing.
Slip resistant:	Non slip surface.
Marker Color:	Green illuminating.
Dimensions:	Photoluminescent stripe width: 1". Length: 48" or custom.
Warranty:	5 year on materials, 25 year on glowing
Green Attributes:	Non-electric. Non-radioactive. No hazardous materials. Long life. Near-zero maintenance.
Listings and Codes:	Listed to UL 1994. IBC, IFC & NFPA compliant.

Active Safety's Series 210 Stair Nosing strip is an aluminum strip installed directly onto the leading edge of stairs or on walls of new and existing buildings for exit pathway markers. This model provides a high quality installation consistent with building architecture and occupant traffic patterns. Automatic operation requires only 1 footcandle of charging illumination under normal conditions. Long life and near zero maintenance ensure the system will always be available to support tenant safety during normal operations and emergencies.

Ordering Format (example: 210 – ALA – F – 1 – C)

SERIES	*CONSTRUCTION*	*PROFILE*	*PHOTOLUMINESCENT STRIPE WIDTH*	*LENGTH*
210 BA - Stair Nosing marker	ALA - Aluminum w/ adhesive back	F - Flat [note 1]	1 - 1"	48 - 48" C - Custom

Specification Description

Photoluminescent Stair Nosing Marker. UL 1994 Listed. Compliant to IBC, NFPA & IFC Codes. Non-electrical, non-radioactive photoluminescent operation. Thin profile aluminum with photoluminescent coating is available in custom lengths. Photoluminescent stripe is 1" wide. 25 foot visibility with 1 foot-candle of charging illumination.

Active Safety Series 210 BA.

Lights on

Lights off

© 2019