



Series 2001 H w handicap

Photoluminescent *Exit Sign* • High & Low Level

Project:
 Type:
 Catalog #:
 By/Date:

Specification Features

Viewing Distance:	50 feet
Operating Life:	25+ years
Activation:	5 foot-candles of artificial lighting.
Face Plate:	Green illuminating heavy duty PVC.
Frame:	Optional Black anodized aluminum.
Letter Color:	Red or Green.
Directional:	Field applied arrows (optional).
Mounting:	Wall, Flag, or Ceiling
Attachments:	Tamperproof metal screws, wall mount.
Dimensions:	Height: 8" Width: 22" Depth: 1/8" to 3/8"
Features:	Non-electrical, non-radioactive, low profile, explosion proof, low maintenance
Warranty:	Limited lifetime warranty.
Green Attributes:	No radioactivity. No power usage. No hazardous materials. Minimal maintenance. Long life. Recyclable.
Listings:	Listed to UL 924 by ETL

Active Safety's Series 2001 H

photoluminescent exit signs are specified by leading architects and engineers for applications requiring a durable, traditional style photoluminescent sign. Typical locations include hotels, condos, schools, retail, offices, hospitals, parking garages, US military facilities and other locations conforming to the IBC, NFPA and UFC codes.

Non-electrical and non-radioactive, Active Safety Series 2001 photoluminescent exit signs are a favorite with green environmentally focused projects.

Photoluminescent operation means there are no electrical connections to engineer, procure and install. Once located adjacent to fluorescent lighting, Active Safety Series 2001 photoluminescent exit signs will operate for 25+ years with only minimal maintenance - no lamps, batteries or radioactive tubes to ever replace or dispose of.

Ordering Format (example: ACTIVE SAFETY 2001 – B – S – WM – R – 2A)

SERIES	STYLE	FACES	MOUNT LOCATION	LETTER COLOR	ARROWS
<u>2001</u>	B – black frame BA – brushed aluminum	<u>S</u> – single <u>D</u> – double	<u>WM</u> – wall mount <u>CM</u> – ceiling or flag mount	<u>R</u> – Red <u>G</u> – Green	'Blank' – no arrows 1A - 1 arrow 2A – 2 arrows

Specification Description

High [or Low Level] Exit Sign. Photoluminescent, non-electrical, non-radioactive, 50 foot visibility rating, 25+ year life. Green illuminating heavy duty PVC construction with black anodized frame and 'field applied' arrows. Single and double sided face configurations consistent with ceiling, flag or wall mount applications as specified on project drawings. Matching bracket for ceiling and flag mount applications.
Active Safety Series 2001.

