



ACTIVE SAFETY

SAFER • LESS EXPENSIVE • SUSTAINABLE

USA 800.657.6324

www.activesafety.com

| |
|------------|
| Project: |
| Arch: |
| Catalog #: |
| Date: |

Series 2002 K18000

Door Kickplate Exit Sign

Photoluminescent • UL924 Listed

Specification Features

| | |
|-------------------|--|
| Viewing Distance: | 75 feet |
| Operating Life: | 25+ years |
| Activation: | 5 foot-candles of LED or Fluorescent lighting |
| Facing: | Heavy duty aluminum or stainless steel stencil face |
| Facing Colors: | Black anodized, brushed aluminum, stainless steel or custom colors. |
| Letter Color: | Green Illuminating |
| Attachments: | Supplied by customer |
| Dimensions: | Height: 10" Width: 34", 40" or 46". Custom sizes available |
| Features: | Non-electrical, non-radioactive, low profile, explosion proof, low maintenance. |
| Warranty: | Limited lifetime warranty. |
| Green Attributes: | No hazardous materials, no radioactivity, activated by nearby light, high percentage of recycled material. Minimal maintenance. Long life. |
| Listings & Codes: | <ul style="list-style-type: none"> • Listed to UL924 • Approved by California State Fire Marshal • IBC, NFPA, IFC & UFC compliant |

Active Safety's Series 2002 K18000 is a unique door "kick-plate" with an integrated full size photoluminescent exit sign. A super durable and attractive 'die-cast' metal faceplate backed by a tough plastic liner make the 2002 K18000 an excellent option for a low level door mount exit sign in hotels, condos, schools, amusement parks, hospitals, US military facilities and other locations conforming to the IBC, NFPA and NFPA codes.

Non-electrical, non-radioactive with a high content of recycled material, Active Safety Series 2002 K18000 photoluminescent exit signs will benefit green environmentally focused projects.

Photoluminescent operation means there are no electrical connections to engineer, procure and install. Located adjacent to LED or fluorescent lighting, Series 2002 K18000 signs will operate for 25+ years with only minimal maintenance - no lamps, batteries or radioactive tubes to ever replace or dispose of.

Ordering Format (example: Active Safety 2002 - K18.000 - 34 - W - A)

| SERIES | STYLE | SIZE | MOUNT LOCATION | COLOR |
|-------------|---------------|--|---|---|
| <u>2002</u> | <u>K18000</u> | <u>34</u> - 34" <u>40</u> - 40" <u>46</u> - 46" <u>C</u> - custom | <u>W</u> - wood <u>G</u> - glass <u>M</u> - metal | <u>A</u> - Brushed Aluminum <u>S</u> - Stainless Steel <u>B</u> - Black Anodized Aluminum |

Specification Description

Low Level Door Kickplate Exit Sign. UL 924 listed. Photoluminescent, non-electrical, non-radioactive, 75 foot visibility rating, 25+ year life. Recycled aluminum or stainless steel construction with heavy duty plastic backing. Die-cut, stenciled faceplate with green symbols. Single Face configuration for low level door mount application.
Active Safety Series 2002-K 18.000.

