



ACTIVE SAFETY

SAFER • LESS EXPENSIVE • SUSTAINABLE

USA 800.657.6324

www.activesafety.com

Project:

Contact:

Catalog #:

Date:

300 Series

Photoluminescent Handrail Marker

Features

Viewing Distance: 25 feet
 Operating Life: 25+ years
 Activation: 1 footcandle of artificial lighting including LED and Fluorescent.
 Marker Composition: Durable photoluminescent coating on PVC or aluminum
 Marker Color: Green illuminating color
 Mounting: Factory or Field applied adhesive
 Dimensions: Width: 1/2" & 1", Length: 4' Flat, 47.5" Curved. Custom sizes, curved or flat.
 Features: Flat and curved profiles for stair handrails. Non-electric. Non-radioactive. No hazardous materials. Easy installation onto a variety of substrates. Automatic operation. Durable. Explosion-proof.
 Warranty: 10 years on materials, 25 years on glow.
 Green Attributes: Non-electric. Non-radioactive. No hazardous materials. Long life. Near-zero maintenance.
 Listings and Codes: UL 1994 listed. IBC, IFC and NFPA Compliant.

Active Safety 300 Series Handrail Marker.

A durable pvc strip with a photoluminescent coating that installs directly onto curved or flat handrails in exit pathways. Available in curved and flat profiles, the marker requires the use of an adhesive for permanent installations. Designed for stairwells and exit passageways requiring a high quality finished appearance, especially in areas with a high traffic load.

Ordering Format (example: 300 – PVC – 1/2 – C)

SERIES	BACKING	WIDTH	LENGTH
300	PVC - PVC *AL - Aluminum	1/2 – 1/2" 1 – 1"	E – 48" flat C – 47.5" curved

* Aluminum handrail is a custom order and not stocked.

Specification Description

Active Safety 300 Series Handrail Marker. Listed to UL 1994. Compliant to IBC, IFC and NFPA codes. Photoluminescent, non-electrical, non-radioactive. PVC with photoluminescent surface. 25 foot visibility rating with 1 footcandle of charging illumination. Flat or curved profiles.

Active Safety 300 Series.

Specifications subject to change!

