

Project:  
Contact:  
Catalog #:  
Date:

## 2001 Series Photoluminescent Exit Sign

### Features

Viewing Distance: 50 feet  
Operating Life: 25+ years  
Activation: 5 foot-candles of LED, fluorescent, mercury vapor or metal halide lighting.  
Face Plate: Green illuminating heavy duty PVC.  
Frame: Black anodized aluminum.  
Letter Color: Red or Green.  
Directional: Field applied arrows (optional).  
Mounting: Wall, Flag, or Ceiling  
Attachments: Tamperproof metal screws, wall mount.  
Dimensions: Height: 8" Width: 15" Depth: 1/8" to 3/8"  
Features: Non-electrical, non-radioactive, low profile, explosion proof, low maintenance.  
Warranty: Limited 10 year materials & 25 year on glow.  
Green Attributes: No radioactivity. No power usage. No hazardous materials. Minimal maintenance. Long life. Recyclable.  
Listings & Codes: Listed to UL 924.  
IBC, IFC & NFPA & UFC compliant.

### Active Safety 2001 Series.

A photoluminescent exit sign specified by leading architects and engineers for applications requiring a durable, traditional style photoluminescent sign. Typical locations include hotels, condos, schools, retail, offices, hospitals, parking garages and US military facilities conforming to the IBC, NFPA and UFC codes.

Non-electrical and non-radioactive, Active Safety Series 2001 photoluminescent exit signs are a favorite with green environmentally focused projects.

Photoluminescent operation means there are no electrical connections to engineer, procure and install. Once located adjacent to lighting, Active Safety Series 2001 photoluminescent exit signs will operate for 25+ years with only minimal maintenance - no lamps, batteries or radioactive tubes to ever replace or dispose of.

### Ordering Format (example: 2001 – U – S – WM – R – 2A)

SERIES	STYLE	FACES	MOUNT LOCATION	LETTER COLOR	ARROWS
2001	'Blank' – black frame U - unframed	S – single D - double	WM – wall mount CM – ceiling or flag mount	R – Red G – Green	'Blank' – no arrows 1A - 1 arrow 2A – 2 arrows

### Specification Description

High [or Low Level] Exit Sign. UL 924 listed. Photoluminescent, non-electrical, non-radioactive, 50 foot visibility rating, 25+ year life. Green illuminating heavy duty PVC construction with black anodized frame and 'field applied' arrows. Single and double sided face configurations consistent with ceiling, flag or wall mount applications as specified on project drawings. Matching bracket for ceiling and flag mount applications.

**Active Safety 2001 Series. Specifications subject to change!**

