



ACTIVE SAFETY

SAFER • LESS EXPENSIVE • SUSTAINABLE

USA 800.657.6324

www.activesafety.com

Project:
Contact:
Catalog #:
Date:

**2002 Series
Photoluminescent Exit Sign**

Features

Viewing Distance: 75 feet
Operating Life: 25+ years
Activation: 5 foot-candles of LED or fluorescent lighting.
Face plate: Heavy duty aluminum stenciled face. Optional (non UL) polycarbonate shield.
Face Plate Colors: Black, white, aluminum and custom colors.
Letter Color: Photoluminescent/green illuminating. Red outline on white and aluminum signs.
Directional: Pop-out chevron arrows with standard sign.
Mounting: Wall, flag and ceiling.
Attachments: Tamper proof metal screws or bracket.
Dimensions: 8" high x 15" wide. 1/4" to 3/8" depth
Features: Architectural "Die-Cut" Design. Non-electrical, non-radioactive, low profile, explosion proof, Limited 10 year materials, 25 year on glow.
Warranty: Limited 10 year materials, 25 year on glow.
Green Attributes: No radioactivity. No power usage. No hazardous materials. Recycled material. Minimal maintenance. Long life. Recyclable.
Listings & Codes: UL 924 Listed. IBC, IFC & NFPA and UFC compliant.

Active Safety 2002 Series photoluminescent exit sign.
A durable, architecturally attractive exit sign specified by leading architects and engineers for hotels, schools, retail, offices, parking garages & other locations. Conforms to the IBC, NFPA and UFC codes.
Non-electrical, non-radioactive and with a high content of recycled material, Active Safety Series 2002 photoluminescent exit signs are a favorite with LEED™ and other environmentally focused projects.
Photoluminescent operation means there are no electrical connections to engineer, procure and install. Once located adjacent to artificial lighting, Active Safety 2002 Series photoluminescent exit signs will operate for 25+ years with only minimal maintenance - no lamps, batteries or radioactive tubes to ever replace or dispose of.

Ordering Format (example: 2002 - S - WM - A)

SERIES	STYLE	FACES	MOUNT LOCATION	FACE PLATE COLOR	ARROWS
2002	<u>BLANK</u> – standard configuration <u>BE</u> – polycarbonate vandal shield	<u>S</u> – single <u>D</u> - double	<u>WM</u> – wall mount <u>CM</u> – ceiling or flag mount	<u>A</u> – brushed aluminum <u>B</u> – black <u>W</u> – White <u>C</u> - Custom	Blank' – no arrows <u>1A</u> - 1 arrow <u>2A</u> – 2 arrows

Specification Description

High [or Low Level] Exit Sign. UL 924 listed. Photoluminescent, non-electrical, non-radioactive, 75 foot visibility rating, 25+ year life. Recycled aluminum construction. Die-cut, stenciled faceplate with green symbols and 'pop-out' arrows. Single and double sided face configurations consistent with ceiling, flag or wall mount applications specified on project drawings. Matching bracket for ceiling and flag mount applications.

Active Safety Series 2002.

Specifications subject to change!



Ceiling Mount



Flush Wall Mount