



ACTIVE SAFETY

SAFER • LESS EXPENSIVE • SUSTAINABLE

USA 800.657.6324
www.activesafety.com

Project:
Contact:
Catalog #:
Date:

2002K Series

Photoluminescent Kickplate Exit Sign

Features

Viewing Distance: 50 feet
 Operating Life: 25+ years
 Activation: 5 foot-candles of LED or Fluorescent lighting.
 Facing: Heavy duty aluminum or stainless steel stencil face.
 Facing Colors: Black anodized, brushed aluminum, stainless steel or custom colors.
 Letter Color: Photoluminescent/green illuminating.
 Attachments: Supplied by customer.
 Dimensions: Height: 10" Width: 34", 40" or 46". Custom sizes available.
 Features: Non-electrical, non-radioactive, low profile, explosion proof, low maintenance.
 Warranty: Limited 10 year materials & 25 year on glow.
 Green Attributes: No hazardous materials, no radioactivity, activated by nearby light, high percentage of recycled material. Minimal maintenance. Long life.
 Listings & Codes: Listed to UL 924.
 IBC, NFPA, IFC & UFC compliant.

Active Safety 2002K Series.

Unique door "kick-plate" with an integrated full size photoluminescent exit sign. A durable and attractive 'die-cast' metal faceplate backed by a tough plastic liner makes the 2002 an excellent option for a low level door mount exit sign in hotels, condos, schools, hospitals, US military facilities and other locations conforming to the IBC, NFPA and NFPA codes.

A high content of recycled material, Active Safety 2002K Series exit signs will benefit green environmentally focused projects.

Photoluminescent operation means there are no electrical connections to engineer, procure and install. Once located adjacent to lighting, Series 2002K signs will operate for 25+ years with only minimal maintenance - no lamps, batteries or radioactive tubes to ever replace or dispose of.

Ordering Format (example: 2002 K - 34 - A)

SERIES	SIZE	COLOR
<u>2002K</u>	<u>34</u> - 34"	<u>A</u> - Brushed Aluminum
	<u>40</u> - 40"	<u>S</u> - Stainless Steel
	<u>46</u> - 46"	<u>B</u> - Black Anodized Aluminum
	<u>C</u> - custom	

Specification Description

Low Level Door Kickplate Exit Sign. UL 924 listed. Photoluminescent, non-electrical, non-radioactive, 50 foot visibility rating, 25+ year life. Recycled aluminum or stainless steel construction with heavy duty plastic backing. Die-cut, stenciled faceplate with green symbols. Single face configuration for low level door mount application.

Active Safety Series 2002K. Specifications subject to change!

