



ACTIVE SAFETY

SAFER • LESS EXPENSIVE • SUSTAINABLE

USA 800.657.6324
www.activesafety.com

Project:
Contact:
Catalog #:
Date:

210 BA Series
Photoluminescent Anti-Slip Nosing Marker

Features

Viewing Distance: 25 feet
Operating Life: 25+ years
Activation: 1 foot-candle of artificial lighting.
Marker Composition: Thin profile aluminum strip with photoluminescent coating.
Mounting: Factory applied adhesive backing.
Slip resistant: Anti-slip surface.
Marker Color: Yellow-green illuminating.
Dimensions: Photoluminescent strip: width: 1" & 2" length: 48" (2" custom order)
Warranty: Limited 5 years on materials, 25 years on glow.
Green Attributes: Non-electric. Non-radioactive. No hazardous materials. Long life. Near-zero maintenance.
Listings and Codes: Listed to UL 1994. IBC, IFC & NFPA compliant.

Active Safety 210 BA Series Anti-Slip Nosing Marker.

An aluminum strip installed directly onto the leading edge of stairs, floors and walls of new and existing buildings for exit pathway markers. This model provides a high quality installation consistent with building architecture and occupant traffic patterns. Automatic operation requires only 1 footcandle of charging illumination under normal conditions. Long life and near zero maintenance ensure the system will always be available to support tenant safety during normal operations and emergencies.

Ordering Format (example: 210 BA – ALA – F – 1 – 48)

SERIES	CONSTRUCTION	PROFILE	PHOTOLUMINESCENT STRIPE WIDTH	LENGTH
<u>210 BA</u> – Anti-Slip Nosing Marker	<u>ALA</u> – Aluminum w/ adhesive back	<u>E</u> - Flat	<u>1</u> - 1" <u>2</u> – 2"	<u>48</u> - 48"



Specification Description

Photoluminescent Stair Nosing Marker. UL 1994 Listed. Compliant to IBC, NFPA & IFC Codes. Non-electrical, non-radioactive photoluminescent operation. Thin profile aluminum with photoluminescent coating is available in custom lengths. Photoluminescent stripe is 1" wide. 25 foot visibility with 1 footcandle of charging illumination.

Active Safety 210 BA Series.
Specifications subject to change