ACTIVE SAFETY
SAFER•LESS EXPENSIVE•SUSTAINABLE

USA 800.657.6324
www.activesafety.com

Project:
Contact:
Catalog #:
Date:

215 Series
Photoluminescent Contrasting Tread Marker

Features

Viewing Distance:	25 feet
Operating Life	25+ years
Activation:	1 foot-candle of artificial lighting including LED & fluorescent.
Marker Composition:	Thin profile steel strip with photoluminescent and black anti-slip coatings.
Mounting:	Client supplied construction adhesive and/or screws.
Slip resistant:	Anti-slip surface.
Marker Color:	Yellow-green illuminating.
Dimensions:	3” width custom length (1” photoluminescent stripe & 2” black anti-slip stripe).
Warranty:	Limited 10 years on materials, 25 years on glow.
Green Attributes:	Non-electric. Non-radioactive. No hazardous materials. Long life. Near-zero maintenance.

Active Safety 215 Series Contrasting Anti-Slip Nosing Tread Marker. Steel strip installed directly onto the leading edge of stairs in new and existing buildings. This model provides a high quality installation consistent with building architecture and occupant traffic patterns. Automatic operation requires only 1 foot-candle of charging illumination under normal conditions. Long life and near zero maintenance ensure the system will always be available to support tenant safety during normal operations and emergencies.

Ordering Format (example: 215 – ST – F – 3 – C)

SERIES	*CONSTRUCTION*	*PROFILE*	*PHOTOLUMINESCENT STRIPE WIDTH*	*LENGTH*
215 – 3” Contrasting Anti-Slip Tread Marker	ST - Steel	F - Flat	3 - 3"	C - Custom"

Specification Description

Photoluminescent contrasting Anti-slip Tread Marker. UL 1994 Listed. Compliant to IBC, NFPA & IFC Codes. Non-electrical, non-radioactive photoluminescent operation. Thin profile steel with photoluminescent coating and anti-slip strip is available in custom lengths. Photoluminescent stripe is 1" wide. 25 foot visibility with 1 foot-candle of charging illumination.
Active Safety 215 Series.
Specifications subject to change.