



ACTIVE SAFETY

SAFER • LESS EXPENSIVE • SUSTAINABLE

USA 800.657.6324

www.activesafety.com

Project:
Contact:
Catalog #:
Date:

PHOTOLUMINESCENT • SERIES 510 • SUSTAINABLE • SAFER • LESS EXPENSIVE

Series 510 EX
Photoluminescent NFPA 170 Exit Marker

Features

<p>Viewing distance: 25 feet Operating Life: 25+ years. Activation: 1 footcandle of artificial lighting including LED and Fluorescent. Marker Composition: PVC placard. Marker Color: Yellow-green illuminating background with green symbols. Mounting: Factory applied adhesive backing or client applied construction adhesive. Dimensions: 5" x 12". Depth: 1/8" Features: Easy installation onto a variety of substrates. Automatic operation Durable. Long life. Near-zero maintenance. Warranty: Limited lifetime. Green Attributes: Non-electric. Non-radioactive. No hazardous materials. Listings and Codes: UL 1994 listed. NFPA, IBC, IFC compliant.</p>	<p>Active Safety Series 510 EX Exit Marker A durable compliant to NFPA 170 placard designed to be installed directly onto walls & doors that lead to final exits. Automatic operation during emergencies requires only 1 footcandle of charging illumination to be present under normal conditions. Long life and near-zero maintenance ensure the system will always be available to support occupant safety.</p>
---	--

Ordering Format (example: 510 – PVC – A – R)

SERIES	CONSTRUCTION	MOUNTING	DIRECTIONAL
510 EX - NFPA 170 exit marker with the word exit	PVC – Plastic	A - factory applied adhesive backing AN - no adhesive backing	R – Running Man Right [default] L – Running Man Left

Specification Description

Photoluminescent NFPA 170 Exit Marker. UL 1994 Listed. Compliant to IBC, NFPA & IFC Codes. Non-electrical, non-radioactive, photoluminescent operation. Durable PVC placard [with or without adhesive backing] and directional running man image [Running man right or running man left]. 25 foot visibility with 1 footcandle of charging illumination. **Active Safety Series 510 EX.** [Brackets denotes options]

