



SAFER • LESS EXPENSIVE • SUSTAINABLE

**USA 800.657.6324**

**www.activesafety.com**

Project:

Contact:

Catalog #:

Date:

## 709 Series

### Photoluminescent Obstacle Marker

#### Features

Viewing Distance:	25 feet
Operating Life:	25+ years
Activation:	1 ft-candle of LED or fluorescent illumination.
Marker Composition:	Vinyl tape with adhesive back.
Marker Color:	Yellow-green illuminating with black stripe.
Directional:	No
Mounting:	High quality factory applied adhesive backing.
Dimensions:	Width: 1", Length: 60 ft.
Features:	Easy installation. Automatic operation. Durable. Near-zero maintenance. Long Life.
Warranty:	Limited 1 year materials & 5 years on glow.
Green Attributes:	Non-electric, non-radioactive, low maintenance, long life.
Listings and Codes:	UL 1994 listed. IBC, IFC & NFPA compliant.

#### Active Safety 709 Series.

A photoluminescent exit path marker that is a durable vinyl tape for marking obstacles. Designed for marking pipes, fire extinguishers and other obstacles. Automatic operation requires only 1 footcandle of charging illumination under normal conditions. Long life and near-zero maintenance ensure the system will always be available to support client safety during normal operations and emergencies.

Ordering Format (example: 709-60-1)

Series	Length	Width
709 - Marker Tape	60 - 60 feet	1 - 1 inch



#### Specification Description

1" Obstacle marker tape. Compliant to UL 1994. Photoluminescent, non-electrical, non-radioactive. 25 feet visibility rating, 25 year life. Polyester tape with high quality adhesive back. Yellow-green illuminating color.

**Active Safety 709 Series.**

**Specifications subject to change.**