



ACTIVE SAFETY

SAFER • LESS EXPENSIVE • SUSTAINABLE

USA 800.657.6324
www.activesafety.com

Project:
Contact:
Catalog #:
Date:

C100 Series Photoluminescent Exit Sign

Features

Viewing Distance: 100 feet
 Location Rating: Wet location, indoor and outdoor.
 Operating Life: 25+ years
 Activation: 5 foot-candles of LED, fluorescent, metal halide or mercury vapor lighting.

Face plate: Injected molded ABS.
 Face Plate Colors: Red, black or green.
 Letter Color: Photoluminescent/green illuminating.
 Directional: Two (2) arrows included.
 Mounting: Wall, flag and ceiling.
 Attachments: T- Bar Bracket with ceiling or flag mount.
 Dimensions: 9.5" high x 17.25" wide. 13/64" depth
 Features: Non-electrical, non-radioactive, explosion proof, low maintenance, UV stable.
 Warranty: Limited 10 year materials & 25 year on glow.
 Green Attributes: No power usage, No radioactivity, No hazardous materials. Minimal maintenance. Long life. Recyclable.
 Listings & Codes: UL 924 Listed. Compliant to IBC, NFPA, IFC & UFC codes.

Active Safety C100 Series.

C100 photoluminescent exit signs are durable exit signs specified by leading architects and engineers for hotels, condos, schools, retail, offices, hospitals, parking garages, US military facilities and other locations conforming to the IBC, NFPA and UFC codes.

Non-electrical and non-radioactive, Active Safety C100 Series photoluminescent exit signs are an excellent choice for environmental focused projects.

Photoluminescent operation means there are no electrical connections to engineer, procure and install. Once located adjacent to an artificial light source, Active Safety Series C100 photoluminescent exit signs will operate for 25+ years with only minimal maintenance - no lamps, batteries or radioactive tubes to ever replace or dispose of.

Ordering Format (example: C100 - S - WM - B)

SERIES	FACES	MOUNTING	FACE PLATE COLOR
C100	S - single D - double	WM – wall mount CM – ceiling or flag mount	B – Black R – Red G – Green

Specification Description

High [or Low Level] Exit Sign. UL 924 listed. Photoluminescent, non-electrical, non-radioactive, 100 foot visibility rating, 25+ year life. ABS plastic construction. Single and double sided face configurations consistent with ceiling, flag or wall mount applications as specified on project drawings. Matching bracket for ceiling and flag mount applications. Directional arrows included.

Active Safety C100 series.
Specifications subject to change!



Red Face



Green



Black