



ACTIVE SAFETY

SAFER • LESS EXPENSIVE • SUSTAINABLE

USA 800.657.6324
www.activesafety.com

Project:
Contact:
Catalog #:
Date:

Ultra 50 Series
Photoluminescent Exit Sign

Features

Viewing Distance: 50 feet
Location Rating: Wet location, indoor and outdoor.
Operating Life: 25+ years
Activation: 5 foot-candles of **LED**, fluorescent, metal halide or mercury vapor lighting.
Face plate: Injected molded ABS.
Face Plate Colors: Red, Black, Green, White or Silver
Letter Color: Photoluminescent Illuminating.
Directional: Two (2) arrows included. Field mounted.
Mounting: Wall, flag and ceiling.
Attachments: T- Bar Bracket with ceiling or flag mount
Dimensions: 9" high x 16" wide. 1/8" to 1/4" depth
Features: Non-electrical, non-radioactive, explosion proof, low maintenance, UV stable.
Warranty: Limited 10 year materials, 25 years glow
Green Attributes: No power usage. No radioactivity. No hazardous materials.
Listings & Codes: Minimal maintenance. Long life. Recyclable. UL 924 Listed. Compliant to IBC, NFPA, IFC & UFC codes.

Active Safety U50 Series.

U50 photoluminescent exit signs are durable exit signs specified by leading architects and engineers for hotels, condos, schools, retail, offices, hospitals, parking garages, US military facilities and other locations conforming to the IBC, NFPA and UFC codes.

Non-electrical and non-radioactive, Active Safety Series U50 photoluminescent exit signs are an excellent choice for environmentally focused projects.

Photoluminescent operation means there are no electrical connections to engineer, procure and install. Once located adjacent to an artificial light source, Active Safety photoluminescent exit signs will operate for 25+ years with only minimal maintenance - no lamps, batteries or radioactive tubes to ever replace or dispose of.

Ordering Format (example: U50 - S - WM - B)

SERIES	FACES	MOUNTING	FACE PLATE COLOR
U 50	S - single D - double	WM - wall mount CM - ceiling or flag mount	B - Black R - Red G - Green W - White S - Silver

Specification Description

High [or Low Level] Exit Sign. UL 924 listed. Photoluminescent, non-electrical, non-radioactive, 50 foot visibility rating, 25+ year life. ABS plastic construction, arrows. Single and double sided face configurations consistent with ceiling, flag or wall mount applications as specified on project drawings. Matching bracket for ceiling and flag mount applications. Directional arrows included.

Active Safety U50 Series
Specifications subject to change



Black



White



Silver



Red



Green